



Specifications	
<b>Material:</b>	Modified impact acrylic for appliqué, tactile signage, front or reverse engraving
<b>Finish:</b>	Matte non-glare
<b>Sheet Size:</b>	24" x 48" (610 x 1219mm)
<b>Thickness 1-Ply:</b>	1/32" (0.8mm) Use LG311 as first digits of item code. 1/16" (1.6mm) Use LG321 as first digits of item code. 1/8" (3.2mm) Use LG341 as first digits of item code. .020" (.5mm) Use LG302 as first digits of item code.
<b>Thickness 2-Ply:</b>	.050" (1.0mm)
<b>Thickness 3-Ply:</b>	NONE
<b>Usage:</b>	Interior & Exterior safety signage. Tactile Signage Exit/Egress Signage Industrial Tags MEA certified (MEA#203-08-M) (Note: The .020 gauge may be used as appliqué.)
<b>Engraving Method:</b>	Laser and Rotating carbide
<b>Cutting Depth:</b>	.022" (.30mm) (Reverse only)
Capabilities	
<b>Scores</b>	■ <b>Bonds</b>
<b>Saws</b>	■ <b>Permits Fine Engraving</b>
<b>Drills</b>	■ <b>UV Stable</b>
<b>Shears</b>	■ <b>Back-Filling</b>
<b>Laser Vector Cuts</b>	■ <b>Back-Lighting</b>
<b>Bevels</b>	■ <b>Braille-Engravable</b>
<b>Heat Bendable</b>	■ <b>Embosses</b>
<b>Screen Prints</b>	■ <b>Ink Prints</b>
<b>Hot Stamps</b>	■ <b>Thermal Prints</b>

Some appliqué colors available in 1mm for European regulations.