

# Vision Max Specialty Engravers

## Technical Specifications



Model	MAX	MAX Pro
Software	Vision Express (Vision Expert or PRO optional)	Vision Expert or PRO optional
Maximum Work Area	8" x 12" (203 x 305mm)	8" x 12" (203 x 305mm)
Maximum Work Piece Clearance	Flat 14"(L) x Any Width x 7"(H) (355 x Any Width x 178mm)	Flat 11.75"(L) x Any Width x 11"(H) (298 x Any width x 280mm)
	Cylindrical 12" x 10" (305 x 254mm) Diameter	Cylindrical 12" x 6" (305 x 152mm) Diameter
Z-Axis Stroke	3" (76mm)	3" (76mm)
Spindle Type	11/64", 6mm or 1/4" Top Loading	11/64", 6mm or 1/4" Top Loading
Resolution / Speed	0.0002" - 10"/sec	0.0002" - 10"/sec
Table Type	Aluminium T-slot, Cylindrical	Aluminium T-slot, Cylindrical
Interface	Ethernet	Ethernet
Controller	Built-In with Series 5 Pendant	Series 5 High-Speed Controller
Warranty	2 Year Limited	2 Year Limited
Power Requirements	220V 10 Amp	220V 10 Amp
Physical Dimensions	28"(W) x 28"(D) x 26"(H)	24"(W) x 17"(D) x 33.5"(H) (610 x 432 x 850mm)
Series 5 Controller Dimensions	N/A	15" (W) x 15" (D) x 4.5" (H) (380 x 380 x 115mm)
Weight (machine)	353lbs (160kg)	320lbs (145kg)
Weight (controller)	N/A	30 lbs (13.5kg)
Additional Options	Top/Bottom Collet, Ring Attachment	Top/Bottom Collet, Ring Attachment