

SDS No: 0046

Section 1. Product and Company Identification	
Product Name:	Naturals
Trade Name:	Film-stamped Impact Modified Acrylic
Recommended Use:	Signage, Other
Restrictions on Use:	None

Manufacture: Rowmark 5409 Hamlet Drive Findlay, OH 45840	In Case of Emergency: Call: Medical:911 Poison Control: 800-589-3897
	Information: Call: 1-877-ROWMARK Email: techhelp@rowmark.com

Section 2. Hazard Identification	
GHS Classification:	Not Classified
GHS Label Elements:	Not Applicable
GHS Rating	
Health	5
Flammability	4
Instability	5
Special	
Other Hazards:	Not Applicable
NEW GHS Hazard Categories	
Category 1 = Severe Hazard	
Category 2 = Serious Hazard	
Category 3 = Moderate Hazard	
Category 4 = Slight Hazard	
Category 5 = Minimal Hazard	

Section 3. Composition / Information on Ingredients			
Name	CAS #	% by Weight	OSHA
P (EA/MMA)	Proprietary	50-54	N
Acrylic Styrene Copolymer	Proprietary	35-50	N
Methyl methacrylate	80-62-6	< 0.5	Y
Ethyl acrylate	140-88-5	< 0.1	Y
Aluminium Flake	7429-90-5	1-5	
Carbon Black	1333-86-4	1-5	
Copper	7440-50-8	1-2	

The substance(s) marked with a "Y" in the OSHA column are identified as hazardous chemicals according to the criteria of the OSHA Hazardous Communication Standard (29 CFR 1910.1200).

While this material is not classified as hazardous under Federal OSHA regulations, this SDS contains valuable information critical to the safe handling and proper use of this product. This SDS should be retained and available for employees and other users of this product.

The components of this product are all on the TSCA Inventory list. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

Section 4. First Aid Measures	
Inhalation:	Dust and process vapors may be irritation to the nose, throat and respiratory tract. Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get Medical attention.
Eyes:	Dust, fines and process vapors may irritate the eyes. Immediately flush eyes with water for at least 15 minutes. Get medical attention.
Skin:	Exposure to molten plastic may cause thermal burns. If molten material comes in contact with the skin, cool under ice water or a running stream.
Ingestion:	No adverse health effects expected from ingestion.

Section 5. Fire-Fighting Measures	
Suitable Extinguishing Methods:	Dry Chemical, Water Spray, Foam Carbon Dioxide. Avoid using direct streams of water on molten burning material.
Unsuitable Extinguishing Methods:	NONE known.
Hazards During Fire-fighting:	Carbon monoxide, carbon dioxide, original monomer other hydrocarbon oxidation products.
Protective Equipment:	Wear self-contained breathing apparatus and protective suit.

Section 6. Accidental Release Measures	
Personal Precautions:	See Section 8 - Exposure Controls / Personal Protection.
Environmental Precautions:	No Special environmental precautions required.